



REMOSMS

REMOSMS

Datasheet

THE STINGER REMOSMS SMS MODULE



1. GENERAL

The Stinger SMS notification facility was developed to increase the level of security at complexes and estates. The increased level of crime necessitates the development of new innovation and since Stinger Electronics is always on the forefront of new innovation in the perimeter security industry, the SMS facility has been added to our extensive list of peripherals.

Different to existing SMS alert systems, the Stinger SMS unit is fully integrated into the BS102/BS120 LCD control unit, and interfaces directly with the Rs485 bus. The message displayed on the LCD screen is identical to the information in the SMS and also includes the site name.

Up to 25 users can be programmed, while each individual zone alarm can be allocated to each user.

2. KEY FEATURES

1. Fully integrated with the BS102/BS120 LCD remote control unit
2. Up to 25 users can be programmed into the unit
3. Each zone alarm can be allocated to a different user
4. Alarm reset can be achieved by simply dialling SMS number
5. Integrated microphone can be used to verify if the alarm was reset
6. Configuration and programming of users is simple via the two-button control unit
7. "Alarm Cleared" SMS will be sent if the alarm was successfully reset
8. The SMS will contain the site name, type of alarm with time and date
9. On screen signal strength indication
10. Optional extended aerial in case of poor reception